

CHEVROLET LIGHTING PROGRAM

TYPE: F17

APPLICATION:

Chevrolet dealership lighting

CONSTRUCTION:

20 ga. steel painted matte black
Formed aperture plate with $\frac{5}{8}$ " lip
Integral adjustable locking mounting bars
Thermally protected
Die-cast lamp housing and heat sink
26w features active cooling module


REFLECTOR CONSTRUCTION:

Spun aluminum self-flanged reflector with angle cut
Variety of anodized aperture finishes in both white and clear flange
Steel mounting ring with torsion spring

MOUNTING:

For use in T-grid or sheet rock ceilings

LABELING:

 pending

26w - 36" marked spacing

OPTICS:

0-40° lockable tilt, 360° + rotation

LED cluster:

Color temp: 3000K

CRI: 85

Life: 50,000 hrs

Lumen Maintenance: >70% of initial lumens

@ 50,000 hrs

Lumen output: 26w 1200 typ (estimated)

16w 800 typ (estimated)

Beam options: Spot 12°, Flood 25°, and Wide Flood 40°

Field interchangeable optics


ELECTRICAL:

Electronic constant current LED driver

120v or 277v input

Optional dimming down to less than 20%, available on 120v only with ELV dimming equipment, consult factory for approved device list

This product complies with IEEE C62.41 for surge endurance up to 2.5KV. Amerlux recommends using additional surge protection with this unit (supplied by others), surge damage is not covered by warranty.



Ceiling Cut Out Dimension: 5 $\frac{7}{16}$ "

CERTIFIED PROGRAM LIGHTING

ORDERING INFORMATION:

Cat #

KRA226LED-SASDLD-WF-VOLT

Amerlux reserves the right to change details that do not affect overall function and performance.

23 daniel road, east, fairfield, nj 07044 • P: 973-882-5010 F: 973-882-2605 • www.amerlux.com

amerlux
GLOBAL LIGHTING SOLUTIONS