

CHEVROLET LIGHTING PROGRAM

SHOWROOM PERIMETER

TYPE:F17D

APPLICATION:

Chevrolet Dealership Lighting

CONSTRUCTION:

20 ga. galvanized steel frame
18 ga. galvanized steel splice housing and hanger brackets
Extruded aluminum heat sink

OPTICS:

Spun aluminum matte semi-diffuse aperture cone
Beam options: Wide Flood (0.9 s/mh)
Very Wide Flood (1.2 s/mh)

LED:

Philips Fortimo DLM 2000 lumen module
Color Temp Options: 3000K or 3500K
CRI: 80 typ.
Life: 50,000 hrs
Lumen Maintenance: >70% of initial
lumens @ 50,000 hrs
Lumen output: 1690 (estimated)

ELECTRICAL:

Electronic constant current LED driver
120v or 277v input
Dimmable to 10%, 0-10v dimming equipment, consult factory for approved device list
This product complies with IEEE C62.41 for surge endurance up to 2.5KV. Amerlux recommends using additional surge protection with this unit (supplied by others), surge damage is not covered by warranty.

MOUNTING:

For use in T-grid or sheet rock ceilings



LABELING:



pending
Wet location (with lens accessory)



Electrostatic sensitive device,
observe precautions for
handling



Ceiling Cut Out Dimension: 6 7/16"

CERTIFIED PROGRAM LIGHTING

10 year limited
warranty
AMERLUX LED

ORDERING INFORMATION:

Cat #

KRA238LED-SDSDLD-WF-VOLT

Amerlux reserves the right to change details that do not affect overall function and performance.